



15112 National Pike, Hagerstown, MD 21740
PHONE (301) 582-0640 FAX (301) 582-3618
info@hagerstowns Speedway.com

Late Model Sportsman and Crate Late Model Sportsman Specifications

Updated June 4, 2019

CAR SPECIFICATIONS

A.) See Late Model Car Specifications or Lucas Oil or World of Outlaw Late Model Car Specifications. A copy of Lucas Oil Car Specifications is included.

358 ENGINE SPECIFICATIONS

- A.) Engines limited to 358 Cubic Inches.
- B.) Block must be a standard production block or approved aftermarket block that was less than 358 cubic inches originally. No aluminum blocks
- C.) Crank minimum weight of 46 lbs.
- D.) RODS- Any rod up to 6 inches. NO TITANIUM RODS.
- E.) Flat top pistons only.
- F.) Any steel head, or DART steel head, valves must be in factory location. Heads must have a 60 cc minimum combustion chamber. **Aluminum heads with 2 barrel 650 carburator**. No relocating rocker arm studs. Rocker shaft systems are allowed.
- G.) Production valve or production replacement, steel or stainless steel only. Any spring, any retainer permitted. Roller rockers permitted. Stock valve guide angle. No relocating valve guides. No titanium except for valve springs, retainers and locks. No valve stem diameter smaller than a 5/16" (.310") Shaft Rocker legal.
- H.) Flat tappet cams only **no rollers**.
- I.) Block must be cast iron.
- J.) Must have a working clutch and starter. Multi-disc clutch permitted.
- K.) Gear drive units permitted.
- L.) No needle bearing cam, crank or rod bearings permitted.

358 WEIGHT LIMIT

- A.) The minimum weight limit is 2300 lbs with driver at the end of race.

OTHER

- A.) All 358 LMS cars must have a "358" decal on the air cleaner or on the front edge of hood in a bright contrasting color for officials to recognize which class the car belongs in.
- B.)

CARBURETORS

- A.) Carburetors - 4 barrel, alcohol or gas permitted.
- B.) Carburetor spacer/adaptor must be no more than one Inch maximum thickness with one gasket between carburetor and spacer/adaptor, and one gasket between spacer/adaptor and intake manifold.
- C.) Gaskets must be no more than 1/8 thickness.

IGNITION:

- A.) battery powered ignition - no magnetos.

LATE MODEL SPORTSMAN TIRES

- A.) Any Hoosier tire, 1300 or harder, must punch a durometer reading of 40 minimum.

Late Model Sportsman Crates Specifications

CRATE ENGINES

- A.) GM 602/604 Crate Engines and Ford M-6007-D347SR/JR Crate Engines. Must have seals in place.

CARBURETORS

- A.) 4 barrel, alcohol or gas permitted.

CRATE WEIGHT

- A.) NO WEIGHT LIMIT IN EFFECT.

CRATE TIRES

- A.) Open tire rule for crate engine cars. Any tire manufacture permitted. Any compound

CRATE OTHER

- A.) All crate cars must have "CRATE" decal in a bright contrasting color located noticeably where officials will recognize which class the car belongs in.